Condensing Unit Cage

PAGE 1 OF 1

Standard Construction:

Material:

1" x 1" 16 gauge Galvanized Steel Tube

 $\frac{13}{16}$ " x $\frac{13}{16}$ " 16 gauge Galvanized Steel Tube

2" x 4" x ½" Steel Plate, four cage feet

#10 x 3/4" Stainless Steel Self-Drilling Screws, eight

3/8" x 2" Stainless Steel Bolts, two

Construction:

MIG Welded

Powder Coated - DuPont CPC Gray powder

Features:

Ships knocked-down for easy storage and transport. Hardware and padlocks included.

Available in pallets quantity of 5.

Can easily be installed by one man.

Removable top and side panel for easy service access.

Powdercoated galvanized steel for long term

SIZES: (HxDxW are Interior Dimensions)

resistance to elements.

10" Clearance between cage and slab for electrical and refrigerant lines.

3" Clearance between cage and slab on all others sides (Anchoring Hardware not included).

Footprint Dimensions

MODEL NUMBER	Ι	D	W	Α	В
CUC403434RR	40"	34"	34"	37"	42.5"
CUC524040RR	52"	40"	40"	43"	46.5"

JOB NAME:

LOCATION:

ARCHITECT:

ENGINEER:

CONTRACTOR:

CONTACT MIAMI TECH INC. FOR ADDITIONAL INFORMATION OR WITH SPECIAL REQUIREMENTS.

3611 NW 74TH ST


WEB: WWW.MIAMITECH.COM EMAIL: SALES@MIAMITECH.COM

MIAMI, FL 33147

PHONE: 305-693-7054

*Concealed interior holes for tamper-resistant installation.

FOOT PRINT



CUCXXXXXXRR

FAX: 305-693-6152

Condensing Unit Cage Product Specifications miamitech inc.

CG DATE 06/24/2015 NOT TO SCALE CUCRR

CHECKED BY: IV DATE 06/24/2015 REVISION: 1

NOTE: ALL DRAWINGS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.